

Sub 91
3. (Amended) The glass substrate according to claim 1, wherein the protective layer is an inorganic layer.

Sub 94
4. (Amended) The glass substrate according to claim 3, wherein the inorganic layer has a compressive stress.

Sub 91
5. (Amended) The glass substrate according to claim 1, wherein the protective layer is an organic layer.

Sub 91
6. (Amended) The glass substrate according to claim 5, wherein the organic layer includes a thermosetting resin.

Sub 92
7. (Amended) The glass substrate according to claim 6, wherein the viscosity coefficient of the thermosetting resin is between approximately seven cp and approximately seventy cp.

Sub 91
8. (Amended) The glass substrate according to claim 1, wherein the protective layer includes one inorganic layer and one organic layer.

Sub 93
9. (Amended) A liquid crystal display device, comprising:
a first substrate and a second substrate;
at least one transparent protective layer formed on an outer surface of the first substrate and the second substrate;

Sub C3
BT
Contd
a transparent electrode formed on an inner surface of the first substrate or the second substrate;

an alignment layer formed on the transparent electrode; and

a liquid crystal layer between the first substrate and the second substrate.

bs
Sub
Q1
15. (Amended) The liquid crystal display device according to claim 14, wherein a viscosity coefficient of the thermosetting resin is between approximately several cp and approximately several ten cp.